

# 2016 MAVERICK™ X® mr

## HIGHLIGHTS

- Rotax® 1000R V-twin engine with high-flow dynamics
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok<sup>†</sup> QE auto-locking front differential
- Intelligent Throttle Control (iTC™)
- Continuously Variable Transmission (CVT) with Zylon<sup>†</sup>-reinforced belt
- Extra low L-gear
- Mid-engine layout for mass centralization
- Double A-arm front suspension with 12 in. (30.5 cm) of travel
- Torsional Trailing A-arms independent rear suspension (TTA) with 12 in. (30.5 cm) of travel
- Front and rear FOX<sup>†</sup> 2.5 PODIUM<sup>†</sup> RC2 Piggyback shocks
- 14-in. ITP<sup>†</sup> SS312 cast-aluminum wheels with 30-in. Gorilla Axle Silverback<sup>†</sup> tires
- Strategically positioned engine air intake and CVT inlets / outlets
- WARN<sup>†</sup> winch
- Analog / Digital gauge
- Adjustable driver's seat and tilt steering
- Passenger handhold and grab bar
- X-package seat trims, graphics and sponsor decals

Not EC homologated

## ENGINE

### 1000R

Type	Rotax 976 cc, V-twin, liquid cooled with strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)
Transmission	CVT with Zylon-reinforced belt, L / H / N / R / P, standard engine brake
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

## SUSPENSIONS

Front Suspension	Double A-arm 12-in. (30.5 cm) travel
Front Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression, rebound and preload adjustments
Rear Suspension	Torsional Trailing A-arms independent rear suspension (TTA) with sway bar 12-in. (30.5 cm) travel
Rear Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression, rebound and preload adjustments

## BRAKES

Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic single-piston calipers

## FEATURES

Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Protection	N/A
Winch	4,500-lb (2,041 kg) WARN winch with roller fairlead	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	240-W from four 60-W projectors with tail lights / brake lights
		Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)

## WARRANTY

EC models : 2-Year Warranty.

All EC models are limited to 15 Kw/20 hp and equipped with EC homologation required equipments including without restriction horn, mirrors and blinkers. EC models engines are compliant with EC standards in force. Towing capacities of EC models respect applicable EC homologation requirements.



Hyper Silver, Black & Octane Blue / 1000R

## TIRES / WHEELS

Front Tires	Gorilla Axle Silverback 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Rear Tires	Gorilla Axle Silverback 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Wheels	14 in. ITP SS312 cast aluminum

## DIMENSIONS / CAPACITIES

L x W x H	118.8 x 67.9 x 76.2 in. (302 x 172 x 194 cm)
Wheelbase	84.3 in. (214.1 cm)
Ground Clearance	15 in. (38 cm)
Dry Weight*	1,297 lb (588 kg)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Glove box: 4.5 gal (17.2 L) Under driver seat: 3.5 gal (13.1 L) Center console: 0.3 gal (1.3 L)
Towing Capacity	N/A
Fuel Capacity	10 gal (37.8 L)

©2015 Bombardier Recreational Products Inc (BRP). All rights reserved. \*™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

**can-am**



Can-AmOffroad.com