

2016 OUTLANDER™ PRO

HIGHLIGHTS

- Rotax® V-twin engine
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 12-in. cast-aluminum wheels
- 26-in. Carlisle ACT HD radial tires
- Reinforced seat skin
- Relocated air intakes
- 1,300-lb (590 kg) towing capacity
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- 5.7-gal (21.4 L) water-resistant rear compartment
- Digitally Encoded Security System (D.E.S.S.™)
- Multifunction digital gauge



Not EC homologated

Light Grey / 650

ENGINE

650

Type	Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

TIRES / WHEELS

Front Tires	Carlisle ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12 in. Cast Aluminum

SUSPENSIONS

Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	Oil

DIMENSIONS / CAPACITIES

L x W x H	86 x 46 x 49.5 in. (218.4 x 116.8 x 126 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	34.5 in. (87.7 cm)
Dry Weight*	726 lb (329 kg)
Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston calipers

FEATURES

Gauge	Multifunction digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	230-W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Protection	N/A	Seat	Reinforced seat skin
		Anti-theft System	Digitally Encoded Security System (D.E.S.S.)

WARRANTY

EC models : 2-Year Warranty.

All EC models are limited to 15 Kw/20 hp and equipped with EC homologation required equipments including without restriction horn, mirrors and blinkers. EC models engines are compliant with EC standards in force. Towing capacities of EC models respect applicable EC homologation requirements.

©2015 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrives GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

can-am



Can-AmOffroad.com