

# 2017 RENEGADE® X® xc 1000R

L7e HOMOLOGATION

## HIGHLIGHTS

- Front and rear FOX† 1.5 PODIUM† RC2 shocks
- Tri-Mode Dynamic Power Steering (DPS)
- Aluminum skid plate
- Aluminum taper-profile handlebar with wind deflectors and square pad
- Visco-Lok‡ QE auto-locking front differential



Model presented:  
Renegade 1000R Triple Black, INT version

## AVAILABLE MODELS

■ Triple Black 1000R (L7e, INT)

ENGINES	1000R
Type	Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
CO Emissions	Euro-2 approved

## SUSPENSIONS

Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	FOX 1.5 PODIUM RC2
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	FOX 1.5 PODIUM RC2

## BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brakes with hydraulic twin-piston caliper

## TIRES (EC approved) / WHEELS

Front Tires	ITP Holeshot ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshot ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12 in. cast aluminum

## DIMENSIONS / CAPACITIES

L x W x H	86 x 46 x 49 in. (218.4 x 116.8 x 124 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	10.5 in. (26.7 cm)
Seat Height	34.5 in. (87.7 cm)
Dry Weight*	692 lb (314 kg)
Rack Capacity	Rear: 35 lb (16 kg)
Storage Capacity	N/A
Towing Capacity	135 kg (300 lb.)
Fuel Capacity	5.4 gal (20.5 L)

## FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	240-W from 4 fender mounted projector beam headlamps (60-W) with tail light / brake light
Protection	Front bumper, aluminum taper-profile handlebar with wind deflectors and square pad, aluminum skid plate	Seat	N/A
EC specificities	Turning lights & brake lights, mirrors, horn, lockable gas cap & storage, 2nd recreation D.E.S.S key (not RF), 2x4 compliant braking system, transmission lockable in park mode	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)

## WARRANTY

EC models : 2 years warranty.

All L7e models are limited to 15 Kw/20 hp and equipped with L7e homologation required equipments. L7e models engines are compliant with L7e standards in force. Towing capacities of L7e models respect applicable L7e homologation requirements.

©2016 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

**can-am**

Can-AmOffroad.com



# 2017 RENEGADE® X® xc 1000R

INTERNATIONAL

## HIGHLIGHTS

- Front and rear FOX† 1.5 PODIUM† RC2 shocks
- Tri-Mode Dynamic Power Steering (DPS)
- Aluminum skid plate
- Aluminum taper-profile handlebar with wind deflectors and square pad
- Visco-Lok‡ QE auto-locking front differential



Model presented:  
Renegade 1000R Triple Black, INT version

## AVAILABLE MODELS

■ Triple Black 1000R (L7e, INT)

ENGINES	1000R
Type	Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	FOX 1.5 PODIUM RC2
Rear Suspension	Torsional Trailing arm Independent rear suspension (TTI) 9.3 in. (23.6 cm) travel
Rear Shocks	FOX 1.5 PODIUM RC2

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEELS	
Front Tires	ITP Holeshot ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshot ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12 in. cast aluminum

DIMENSIONS / CAPACITIES	
L x W x H	86 x 46 x 49 in. (218.4 x 116.8 x 124 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	10.5 in. (26.7 cm)
Seat Height	34.5 in. (87.7 cm)
Dry Weight*	692 lb (314 kg)
Rack Capacity	Rear: 35 lb (16 kg)
Storage Capacity	N/A
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	240-W from 4 fender mounted projector beam headlamps (60-W) with tail light / brake light
Protection	Front bumper, aluminum taper-profile handlebar with wind deflectors and square pad, aluminum skid plate	Seat	N/A
		Anti-theft System	RF Digitally Encoded Security System (RF D.E.S.S.)

## WARRANTY

INT models : 2 years warranty.

©2016 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrives GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations requirements.

**can-am**



Can-AmOffroad.com